

FLIR ELARA™ FC-SERIES O

Thermal Security Camera



The Elara™ FC-Series O thermal security camera is one of FLIR's premium thermal security cameras for perimeter protection.

The Elara FC-Series O integrates with external video analytics devices, such as FLIR's TRK or third party solutions, to classify human or vehicular intrusions.

The Elara FC-Series O also offers a wide range of high-performance lenses, with a choice of resolutions, offering greater flexibility for tailoring security systems to specific site conditions.



EASY INTEGRATION WITH ANALYTICS SYSTEMS

The FC-Series O is an ideal camera for integrating with external video analytics systems.

- Fully integrated and certified to work with third party video management systems
- Supports open standard, ONVIF-compliant
- Advanced integration features, such as thermal configuration and alarm management, with FLIR's United VMS
- Target hand-off to PTZ camera auto-tracking

INDUSTRY-LEADING IMAGE QUALITY

Superior thermal image quality in low-contrast conditions.

- Superior image quality in extreme environments
- Custom AGCs provide unmatched image contrast
- Digital Detail Enhancement (DDE) produces sharp edges that improve performance of analytics

HIGH-PERFORMANCE LENSES

Choose from a wide range of high-performance lenses for optimal detection ranges in all conditions.

- Choose from 17 high performance lenses suitable for any perimeter or open area, including QVGA from 4° to 69° fields of view and VGA from 8° to 90° fields of view
- High-performance optics deliver crisp, clean thermal video
- High analytic ranges reduce number of cameras and total cost of ownership (TCO)
- High performance optics deliver clear thermal video

SPECIFICATIONS

Thermal Camera Specifications	
Model	Elara FC-3XX O Elara FC-6XX O
Array Format	320 x 240 640 x 480
Detector Type	Uncooled VOx Microbolometer
Spectral Range	7.5 μm – 13.5 μm
Effective Resolution	76800 307200
Pixel Pitch	FC-369 O 34 μm FC-344 O 34 μm FC-332 O 34 μm Other models 17 μm
Thermal Frame Rate	NTSC: 30 Hz, PAL: 25 Hz / 8.3 Hz
E-Zoom	4x continuous E-Zoom
Focus	Athermalized, focus-free
Sensitivity	< 35 mK for F# 1.0 optics
Video	
Composite Video NTSC or PAL	Hybrid system with IP & analog video, Dynamic NTSC or PAL settings
Analog Video Output Composite	1x Vp-p (PAL or NTSC), 1x BNC 75 Ω
Video Compression	Two independent channels of H.264 (Restricted VBR and CBR, 10 kbps – 4 Mbps, MPEG4, and MJPEG)
Streaming Resolution	D1: 720 x 576, 4CIF: 704 x 576, Native: 640 x 512, Q-Native: 320 x 256, CIF: 352 x 288, QCIF: 176 x 144
Thermal AGC Modes Features	Brightness, contrast, sharpness, gray shade compression, gamma, smart screen balance
Thermal AGC Region of Interest (ROI)	Default, presets and user-definable to ensure optimal image quality of subjects of interest
Image Uniformity Optimization	Automatic Flat Field Correction (FFC); Thermal and Temporal Triggers
SD Card Snapshot Capture	Support for 32 GB SD Card (sold separately)
System Integration	
Ethernet	10/100 Mbps
External Analytics Compatible	Yes
Control Input/Output	1x dry contact in; 1x relay out (rated load .025 A at 5 VDC)
Network APIs	FLIR SDK, FLIR CGI, ONVIF Profile S
Network	
Supported Protocols	IPv4, HTTP, Bonjour, UPnP, DNS, NTP, RTCP, TCP, UDP, ICMP, IGMP, DHCP, ARP, SCP, FTP, RTP/RTSP, Unicast/Multicast, TCP/IP, HTTP, IEEE 802.1X, SNMP
General	
Weight Without Sunshield	1.8 – 2.2 kg (4 – 4.75 lb)
Weight With Sunshield	2.2 – 2.5 kg (4.75 – 5.5 lb)
Dimensions (L, W, H) Without Sunshield	259 x 114 x 106 mm (10.2" x 4.5" x 4.2")
Dimensions (L, W, H) With Sunshield	292 x 129 x 115 mm (11.1" x 5.1" x 4.5")
Power Consumption (Heater Off)	<5.5 W to <8 W (varies by model)
Power Consumption (Heater at 100%)	<25 W to <32 W (varies by model)
Surge Immunity on AC Power Lines	CE: EN55032 Class A; FCC 47 CFR Part 15, Subpart B, Class A (within CISPR 22:2008 Class A limits)
Surge Immunity on Signal Lines	EN 55024: 2010 and 55032: 2010 to 4.0kV on AC aux power lines; EN 50130-4:2011; IEC 62599-2:2010

Cyber Security	
IEEE 802.1x TLS/HTTPS User Authentication Access Control via Firewall Digest Authentication	
Environmental	
IP Rating (Dust/Water Ingress)	IP66 & IP67
Operating Temp. Range	-50°C to 70°C (-58°F to 158°F)
Storage Temp. Range	-50°C to 85°C (-58°F to 185°F)
Humidity	0 – 95% relative humidity
Shock	MIL-STD-810G "Transportation"
Vibe	IEC 60068-2-27
Vandalism	IK10 (except windows)
Anti-Icing	MIL-STD-810 F, Method 521.2 - 6 mm ice, 120 minutes with POE+, 4 mm ice with POE af FC-304, FC-305, FC-610 & FC-608 with Cold Weather kit
Warranty & Regulatory	
Approvals	CE: EN55032 Class A; FCC 47 CFR Part 15, Subpart B, Class A (within CISPR 22:2008 Class A limits)
Certifications	IEC 60068-2-1:2007; IEC 60068-2-2:2007; ISTA-1A (Handling)
Compliance	RoHS Directive 2011/65/EU; WEEE 2012/19/EU
Warranty	Camera: 3 years; Sensor: 10 years

Specifications are subject to change without notice.
For the most up-to-date specs, go to www.teledyneflir.com

AMERICAS

6769 Hollister Ave.
Goleta, CA 93117

EMEA

Luxemburgstraat 2
2321 Meer
Belgium

APAC

Rm 1613-16, Tower II
Grand Central Plaza
138 Shatin Rural Committee Rd.
Shatin, New Territories
Hong Kong

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited. For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact exportquestions@flir.com. ©2022 Teledyne FLIR, LLC. All rights reserved.

Revised on 02/01/22
Elara™ FC-Series O_Datasheet-LTR 20-0884